

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE

MATERIAL NAME	: EMOKUT-16
USES	: MINERAL BASED WATER SOLUBLE METAL WORKING FLUID
MANUFACTURER	: Emulsichem Lubricants Pvt Ltd T-120, MIDC, Bhosari, Pune-411026, Maharashtra, India
Emergency Contact Number	: Tel-+91 20 27120266/77, +91 9822064232 E-mail:- <u>abhijeetbhosale@emulsichem.com</u>

2. COMPOSITION/ INFORMATION ON INGREDIENTS:

Preparation Description

: Blended with emulsifiers, Synthetic ester, Water, Biocides and highly refined mineral Oils.

3. HAZARDS IDENTIFICATION:

Health Hazards

Safety Hazards

Environmental Hazards

4. FIRST AID MEASURES: General Information

Skin Contact

: It is not expected to be a health hazard When used under normal conditions and Controlled working Parameters like Concentration, pH and Filtration. Prolonged skin contact may Cause some disorder like acne and rashes. Impurities in used oil can Be avoided by regular filtration of chips.

- : Not classified as flammable, but will burn
- : Not classified as dangerous for the Environment
- : No treatment is necessary. But may obtain Medical Advice.
- : For repeated skin contact flush with water And wash Hands with soap. Remove the Contaminated clothing. With persistent Irritation, please seek medical Attention.

Page 1 | 4

Emulsichem Lubricants

Emokut 16 ver. 1.1



Eye Contact	: Flush with generous amount of water. If irritation Persists, seek medical advice.
Ingestion	: No treatment is necessary unless large Quantities are taken. In such cases please Seek medical attention.
Notes to Physician	: Please treat as per the symptoms with The product Information

5. FIRE FIGHTING MEASURES

Flash Point	: NA
Auto Ignition temperature	: NA
Flammable Limits in air % by vol.: NA	
Extinguishing Media	: Chemical foam type, Dry powder,
	Carbon di Oxide
Special Information	: NA

6. ACCIDENTAL RELEASE MEASURES

Please avoid contact with spilled material. For further information on Protective Equipment see chapter 8 and for disposal of spilled material see Chapter 13 of the MSDS. If possible eliminate all ignition points, sources.

	Protective Measures	: Avoid contact and prevent from spreading Or Entering drains or water.	
	Cleaning Measures	: Soak up with absorbent material like cloth , sand or other suitable material. Dispose as Per guidelines.	
7.	HANDLING ANS STORAGE		
	Handling	: While handling drums, use safety shoes	
		And other Protective gear and handling Equipment's.	
	Champion and		E
	Storage	: Store in cool properly ventilated area. Storage Temperatures: 5-45 ° c	
8.	8. EXPOSURE CONTROL/ PERSONAL PROTECTION		
	Respiratory	: Under normal conditions, no protection is	
	Respiratory	Required.	
	Eye	: Wear safety glasses if coolant splashes are Likely to Occur.	

Page 2 4Emulsichem LubricantsEmokut 1	6 ver. 1.1
---	------------



Hand

: If required hand gloves may be used. Personal Hygiene is a must in case of Using hand gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance
Odour
Solubility
Density @ 27° C gm/ml
pH of 5% Emulsion
% volatiles by volume @ 21°c
Boiling Point
Melting Point
Vapour Density (Air)
Vapour pressure (mm Hg)
Evaporation Rate

: Golden Yellow
: Slight Odour
: Miscible
: 0.86 ± 0.02
: 9.2 ± 0.3
: NA
: Above 160° c
: NA
: No data available
: No data available
: No evaporation at room temperature

10. STABILITY AND REACTIVITY

Stability Hazardous decomposition

Hazardous Polymerization Conditions to avoid

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute Dermal toxicity

Skin irritation

Eye irritation

Respiratory irritation

Carcinogenicity

- : Stable at room temperature
- No hazardous products are formed
 During Products normal storage and use
 No polymerization occurs
- : Direct sunlight and extreme pressure
- : Expected to be of low toxicity
- : Expected to be of low toxicity
- : Expected to be slightly irritating
- : No irritation
- : No irritation
- : Components are not known to be associated With Carcinogenic effects at the usage doses.

Page 3 | 4

Emulsichem Lubricants

Emokut 16 ver. 1.1



12. ECOLOGICAL INFORMATION

Environmental toxicity

: May cause physical fouling of aquatic Organisms if Left untreated. Not readily Biodegradable.

13. DISPOSAL CONSIDERATIONS

The product can be treated in the ETP before disposing. It the responsibility of the Waste generator to determine the toxicity and physical properties of the material Generated after treatment with proper classification and disposal compliance.

14. TRANSPORT INFORMATION

Domestic (Land)

: This is not classified as dangerous

15. REGULATORY INFORMATION

The Factories Act, 1948, The Second Schedule: Permissible levels of certain Substances in work environment

16. OTHER INFORMATION

MSDS effective date

: 01.01.2017



DISCLAIMER

This information is furnished without warranty, expressed or implied, except that It is accurate to the Best knowledge of Emulsichem Lubricants Pvt Ltd. The data On this sheet are related only on the specific Material designated herein. Emulsichem Lubricants assumes no legal responsibility for use or reliance Upon These data and the damages to life, property incurred thereafter.

Page 4 | 4

Emulsichem Lubricants

Emokut 16 ver. 1.1